


Полужесткие коаксиальные кабели серии SR-L

Product Type		SR-L086		
Structure Drawing				
Structure Characteristics				
Structure	Item	Standard Value		
Inner Conductor	Material	Silver Plated Copper		
	Construction(mm)	1/0.56		
	Nom.Dia(mm)	0.56		
Insulation	Material	LD-PTFE		
	Nom.Dia(mm)	1.68		
Outer Conductor	Material	Ternary Alloy Plated Seamless		
	Nom.Dia(mm)	2.20		
Electrical Characteristics				
Item	Standard Value	Attenuation and Power handling@25°C and Sea Level		
		Frequency (MHz)	Attenuation (dB/m)	Power handling (w)
Impedance (Ω)	50±2	500	0.41	367
Capacitance(pF/m)	88	1000	0.58	259
Velocity(%)	76	3000	1.02	148
Signal Delay (ns/m)	4.3	5000	1.32	115
Max Operating Voltage(v)	1500	6000	1.45	104
		10000	1.88	80
Cut-off Frequency(GHz)	40	18000	2.56	59
		26500	3.13	48
Screening Effectiveness(dB)	120	31000	3.51	42
		40000	3.89	39
Mechanical & Environmental Characteristics				
Min Bending Radius/Single		mm	7.0	
Weight		kg/M	0.019	
Operating Temperature		°C	-55-+200	